Space & Astronomy | Dec 31, 2025 | 8 min read | By Bryan White

Harvesting the Void: The Engineering Behind Space-Based Solar

Environment * Space * Astronomy

Introduction: Orbital Solar Harvesting and Inverse Engineering

The global transition to a decarbonized electrical grid faces a fundamental physical bottleneck: the intermittency of terrestrial renewable generation. Surface solar photovoltaic (PV) arrays are constrained by the diurnal cycle, seasonal insolation swings, and atmospheric attenuation from clouds and aerosols, necessitating massive utility-scale battery or pumped-hydro storage to supply continuous baseload power.[1] Space-Based Solar Power (SBSP) bypasses these terrestrial constraints by placing solar collectors directly into Geostationary Earth Orbit (GEO). In GEO, a satellite remains illuminated for over 99% of the year -- experiencing only brief equinox eclipses -- and intercepts unattenuated solar radiation at an irradiance of approximately 1,360 W/m , roughly 30% higher than peak sea-level insolation.[2] Consequently, an orbital solar array generates roughly eight times more annual energy per unit area than an equivalent terrestrial installation.[3]

For decades after Peter Glaser's 1968 SBSP proposal, orbital power concepts relied on monolithic, kilometer-scale rigid trusses requiring hundreds of heavy-lift launches and complex extravehicular assembly.[4] Beginning in 2013 through a $100 million philanthropic commitment from the Donald Bren Foundation, the Space Solar Power Project (SSPP) at the California Institute of Technology (Caltech) -- led by Professors Harry Atwater, Ali Hajimiri, and Sergio Pellegrino -- fundamentally redesigned the SBSP paradigm.[3][5]

Rather than designing for peak efficiency first and treating cost as an afterthought, the Caltech team applied an "inverse engineering" methodology:[3]

* Levelized Cost Target: To compete economically with terrestrial renewables and nuclear baseload, hardware manufacturing costs were capped at roughly $100 per square meter.[3]

* Areal Mass Constraint: To keep rocket launch costs viable, the target specific mass of the integrated structure was restricted to <150 g/m -- an order of magnitude lighter than conventional spacecraft solar arrays (1,000-3,000 g/m).[6]

* Integrated Flexible "Tiles": Meeting these constraints required eliminating heavy cover glass, thick copper busbars, and mechanical gimbals in favor of modular, origami-folded membrane tiles that combine photovoltaic conversion and radio-frequency (RF) phased-array transmission within a single ultralight sheet.[2][3]

The Space Solar Power Demonstrator (SSPD-1) Architecture

On January 3, 2023, Caltech launched the 50-kilogram Space Solar Power Demonstrator (SSPD-1) aboard a Momentus Vigoride-5 orbital transfer vehicle on a SpaceX Falcon 9

(Transporter-6 mission).[4] Operating in Low Earth Orbit (LEO) for ten months, SSPD-1 subjected three core sub-architectures to the orbital thermal-vacuum and radiation environment.[4][9]

| Experiment | | Full Designation | | Primary Engineering Objective | | Core Hardware & Material Innovation |

| MAPLE | | Microwave Array for Power-transfer Low-orbit Experiment | | Validate electronic beam steering and space-to-ground power transfer | | Custom flexible CMOS RF integrated circuits on polymer PCBs |

| DOLCE | | Deployable on-Orbit ultraLight Composite Experiment | | Verify zero-G unfurling kinematics of a 1.8m x 1.8m modular frame | | Ultrathin carbon-fiber TRAC longerons (~99 g/m skeleton mass) |

| ALBA | | Italian for "Dawn" (Photovoltaic Testbed) | | Quantify orbital radiation and thermal degradation across 32 PV cells | | Spalled III-V Gallium Arsenide (GaAs), perovskites, CIGS, quantum dots |

MAPLE: Flexible Phased-Array Wireless Power Transfer

To eliminate heavy mechanical steering gimbals, the MAPLE payload demonstrated electronic beam steering via constructive and destructive interference across a 2D phased array of flexible microwave transmitters.[7] By adjusting the relative phase timing of each transmitter element at sub-nanosecond resolution, the emitted electromagnetic wavefronts combine coherently in a targeted focal direction while canceling out in sidelobe directions.[7]

Whereas conventional military radar phased arrays require rigid, dimensionally stable backplanes, the SSPP architecture operates on compliant, non-flat membranes that bend and warp under thermal gradients. MAPLE validated custom complementary metal-oxide-semiconductor (CMOS) integrated circuits capable of dynamically recalibrating element phases in real time to compensate for structural flexure.[7] In initial orbital tests in March 2023, MAPLE selectively illuminated two distinct receiver LEDs mounted roughly one foot from the transmitter panel, switching power between them electronically with zero moving parts.[7][9]

On May 22, 2023, MAPLE executed the first space-to-ground wireless power transmission from a flexible array.[1][3] As the spacecraft passed over southern California, a rooftop receiver at Caltech's Gordon and Betty Moore Laboratory of Engineering locked onto the transmitted microwave carrier at the predicted time and frequency, exhibiting the exact Doppler shift dictated by the satellite's LEO velocity.[3][7]

DOLCE and ALBA: Ultralight Deployment Kinematics and Photovoltaic Survivability

The DOLCE experiment tested the structural deployment mechanics of a 1.8-meter by 1.8-meter prototype frame utilizing TRAC (Triangular Rollable And Collapsible) longerons fabricated from ultrathin carbon-fiber composites.[6] Like a carpenter's tape measure, the curved cross-section of a TRAC longeron provides high bending stiffness when extended, yet flattens to coil tightly around a compact central spool for launch, achieving a structural areal density of just 99 g/m .[6][8]

During orbital deployment, DOLCE encountered two instructive mechanical anomalies that had not manifested in terrestrial 1-G testing:[9]

* Cable Snag Recovery via Thermal Expansion: During initial unfurling, a tensioning wire linking the diagonal booms snagged in microgravity. Using a ground-based digital twin to diagnose the geometry, engineers waited for orbital insolation to heat the snagged bracket; the resulting thermal expansion released the wire automatically.[9]

* Actuator Vibration Clearing: When a portion of the composite strip later jammed inside the deployment mechanism, the ground team commanded the deployment motors to oscillate rapidly, shaking the jam free and achieving complete structural deployment.[9]

Concurrently, the ALBA payload monitored 32 distinct photovoltaic cells across 240 days in orbit, recording over 3 million current-voltage (I-V) data points under unshielded UV and Van Allen belt proton/electron bombardment.[3][10] While lead-halide perovskite cells exhibited wide performance variability due to outgassing and ion migration, III-V Gallium Arsenide (GaAs) cells fabricated via controlled spalling -- in which a sub-micron active film is peeled from a reusable germanium/GaAs mother wafer -- demonstrated exceptional radiation hardness, high conversion efficiency, and minimal specific mass throughout the mission.[3][10][11]

Comparative Architecture Analysis and Scaling Challenges

The completion of SSPD-1 in November 2023 confirmed the viability of modular, flexible space solar architecture while clarifying the engineering hurdles required to scale from a 1.8-meter demonstrator to kilometer-scale constellations.[9][12]

| Architectural Parameter | | Legacy 1970s NASA/DOE Reference Concept | | Caltech SSPP Modular Tile Architecture |

| Primary Structure | | Rigid Aluminum/Composite Truss Grid | | Flexible Carbon-Fiber TRAC Membrane |

| Power Bus Distribution | | High-Voltage Copper Cabling & Slip Rings | | Local Tile-Level DC-to-RF Conversion (Zero Bus Cables) |

| Beam Pointing Mechanism | | Kilometer-Scale Mechanical Gimbal Dish | | Distributed Electronic Phased Array (Solid-State) |

| Target Areal Density | | >5,000 g/m | | <150 g/m (99 g/m demonstrated on DOLCE frame) |

| On-Orbit Assembly | | Astronaut EVA & Heavy Robotic Cranes | | Autonomous Strain-Energy Unfurling |

| Fault Tolerance | | Single-Point Failure on Central Bus/Gimbal | | Graceful Degradation Across Millions of Independent Tiles |

Transitioning toward operational prototypes requires solving two primary physical challenges: monolithic layer integration -- reducing total tile density from current ~1,500 g/m breadboards down to the 150 g/m target by laminating spalled GaAs photovoltaics, CMOS phase shifters, and patch antennas into a single film -- and radiative thermal management, dissipating hundreds of megawatts of conversion waste

heat into the vacuum of space without warping the ultra-thin polymer substrates.[2][12][13]

Conclusion: From Orbital Proof-of-Concept to Commercial Constellations

The Caltech Space Solar Power Demonstrator (SSPD-1) retired the core physical risks of ultralight orbital solar power.[9] By validating dynamic phase-calibrated wireless power transmission to Earth via MAPLE, demonstrating sub-100 g/m rollable composite deployment via DOLCE, and proving the orbital durability of spalled GaAs thin films via ALBA, the SSPP has transformed space-based solar power from theoretical paper studies into tested aerospace hardware.[3][7][9]

Updates... (Nov 21, 2026): Corrected author attribution and conference publication metadata for the perovskite radiation study (Huang, Kelzenberg, & Espinet-Gonz lez, Jun 1, 2017), replaced the unreachable Caltech SSPP timeline URL and arXiv preprint with Caltech official mission reports (Jun 1, 2023; Jan 16, 2024) and the peer-reviewed Acta Astronautica MAPLE paper (Ayling et al., Aug 8, 2024), and added exact publication dates across all references.

References & Primary Sources

* [1] ScienceAlert (Jun 6, 2023). Scientists Beam Solar Power From Space to Earth in World First. -- https://www.sciencealert.com/scientists-beam-solar-power-from-space-to-earth-in-world-first

* [2] Gdoutos, E., Leclerc, C., Royer, F., et al. (Jan 7, 2018). A lightweight tile structure integrating photovoltaic conversion and RF power transfer for space solar power applications. 2018 AIAA Spacecraft Structures Conference. -- https://doi.org/10.2514/6.2018-2202

* [3] Caltech Magazine (Oct 16, 2023). Space Solar Power Project Will Harness the Sun to Power the Planet from 300 Miles Above. -- https://magazine.caltech.edu/post/sspp-space-solar-power-project

* [4] California Institute of Technology (Jan 16, 2024). Space Solar Power Project Ends First In-Space Mission with Successes and Lessons. -- https://www.caltech.edu/about/news/space-solar-power-project-ends-first-in-space-mission-with-successes-and-lessons

* [5] Irvine Company (Jul 30, 2021). $100M gift from Irvine Co.'s Bren powers Caltech space electricity idea. -- https://www.irvinecompany.com/press-release/100m-gift-from-irvine-co-s-bren-powers-caltech-space-electricity-idea/

* [6] Gdoutos, E. E., Sommer, C., Truong, A., Wen, A., Pedivellano, A., Royer, F., & Pellegrino, S. (Jan 3, 2022). Development of the Deployable on-Orbit ultraLight Composite Experiment (DOLCE) for the Space Solar Power Project (SSPP) Demonstration Mission. AIAA SciTech Forum. -- https://doi.org/10.2514/6.2022-1266

* [7] Ayling, A., Fikes, A. C., Mizrahi, O. S., Wu, A., Hashemi, S. S., et al. (Aug 8, 2024). Wireless power transfer in space using flexible, lightweight, coherent arrays. Acta Astronautica, 224, 226-243. -- https://doi.org/10.1016/j.actaastro.2024.08.006

* [8] Lee, N., & Pellegrino, S. (Jan 10, 2014). Self-Supporting Membrane Structures

with Curved Creases for Smooth Packaging and Deployment. AIAA Spacecraft Structures Conference. -- https://doi.org/10.2514/6.2014-1037

* [9] California Institute of Technology (Jun 1, 2023). In a First, Caltech's Space Solar Power Demonstrator Wirelessly Transmits Power in Space. -- https://www.caltech.edu/about/news/in-a-first-caltechs-space-solar-power-demonstrator-wirelessly-transmits-power-in-space

* [10] Kelzenberg, M. D., et al. (Jun 9, 2024). Results of the Alba Mission. 2024 IEEE 52nd Photovoltaic Specialist Conference (PVSC). -- https://doi.org/10.1109/pvsc57443.2024.10749564

* [11] Huang, J.-S., Kelzenberg, M. D., Espinet-Gonz lez, P., Mann, C. J., et al. (Jun 1, 2017). Effects of Electron and Proton Radiation on Perovskite Solar Cells for Space Solar Power Application. 2017 IEEE 44th Photovoltaic Specialist Conference (PVSC), pp. 1248-1252. -- https://doi.org/10.1109/pvsc.2017.8366410

* [12] The Space Review (Nov 13, 2023). A small step forward for space-based solar power technology. -- https://www.thespacereview.com/article/4691/1

* [13] pv magazine USA (Oct 22, 2025). Researchers envision a 'bright harvest' from space-based solar power. -- https://pv-magazine-usa.com/2025/10/22/researchers-envision-a-bright-harvest-from-space-based-solar-power/