Space & Astronomy | Jan 17, 2026 | 8 min read | By Bryan White

History in Motion: The Artemis II Rollout to Complex 39B, January 17th 2026

Space * Astronomy * Solar System

Introduction: The Threshold of Lunar Return

On Saturday, January 17, 2026, at approximately 7:00 a.m. EST, the High Bay doors of the Vehicle Assembly Building (VAB) at NASA's Kennedy Space Center retracted, initiating the 4.2-mile rollout of the integrated Space Launch System (SLS) Block 1 vehicle and Orion spacecraft (named Integrity) to Launch Complex 39B.[1][2] Serving as the operational transition from vertical integration to launch pad readiness ahead of February wet dress rehearsals (WDR), the rollout inaugurated Artemis II -- the first crewed lunar mission since Apollo 17 in December 1972, which subsequently launched on April 1, 2026, and completed a 10-day circumlunar flight with Pacific splashdown on April 10, 2026.[1][5][9][10]

Transporting the 11-million-pound combined stack -- comprising the Mobile Launcher (ML), the 322-foot SLS rocket, and the Orion spacecraft configured for Commander Reid Wiseman, Pilot Victor Glover, and Mission Specialists Christina Koch and Jeremy Hansen[1][3] -- tests heavy structural transport mechanics while bringing to the pad key engineering modifications developed after Artemis I. Foremost among these are the thermodynamic and trajectory resolutions to the Orion Avcoat heat shield char-loss anomaly, the staged High Earth Orbit (HEO) checkout profile, and closed-loop human Environmental Control and Life Support System (ECLSS) validation.[13][16]

Heavy Transport Mechanics and Integrated Propulsion Architecture

Moving the integrated SLS stack across the 4.2-mile Alabama river-rock crawlerway at ~0.8 to 1.0 mph (an 8-to-12-hour transit) relied on Crawler-Transporter 2 (CT-2).[1][4] Upgraded through Phase I and II structural modifications, CT-2 utilizes two 1,500-kilowatt AC generators driven by Alco diesel engines to power 16 traction motors across four double-track corner trucks, coupled with strain-gauge-verified track shoes.[4][6] Because the 322-foot SLS possesses a high center of gravity, verticality within +/-10 arcminutes -- particularly when ascending the 5-degree incline to the Pad 39B hardstand -- is maintained by a closed-loop Jacking, Equalizing, and Leveling (JEL) hydraulic system monitored by laser leveling and pressure transducers.[6][7][8] Rollout flight rules prohibited transit if lightning probability within 20 nautical miles exceeded 10%, sustained winds exceeded 40 knots, or ambient temperatures fell outside the 40 deg F-95 deg F foam-protection envelope.[1]

| Parameter | | Artemis II Specification | | Operational Context & Completed Flight Record |

| Rollout & Launch Dates | | Jan. 17, 2026 rollout; Apr. 1, 2026 launch | | 4.2-mile rollout via CT-2; launched following Feb.-Mar. WDR hydrogen and ICPS helium repairs;

splashed down Apr. 10, 2026.[1][5][9] |

| Prime Mover | | Crawler-Transporter 2 (CT-2) | | 11-million-lb load; upgraded 1,500 kW generators & JEL hydraulics[4][6] |

| Launch Vehicle | | SLS Block 1 (8.8M lbs thrust) | | Core Stage (4 RS-25 engines) + twin 5-segment SRBs + RL10 ICPS[10][11] |

| Mission Duration & Crew | | ~10 Days (Apr. 1-10, 2026; 4 Astronauts) | | Reid Wiseman, Victor Glover, Christina Koch, Jeremy Hansen aboard Orion Integrity; max distance 252,756 miles from Earth.[3][13][19] |

| Orbital Checkout Profile | | LEO (115x1,800 mi) -> HEO (235x68,000 mi) | | High-orbit ECLSS checkout & manual proximity operations gate executed[13][14] |

| Reentry Trajectory | | Modified Hybrid / "Loft" Entry | | Shortened heating dwell time to prevent Avcoat gas-pressure spallation; Pacific recovery off San Diego by USS John P. Murtha.[17][19] |

The flight stack integrates Shuttle-derived propulsion with deep-space avionics:[11]

* Core Stage and Five-Segment SRBs: The 212-foot Core Stage stores 730,000 gallons of cryogenic liquid hydrogen and liquid oxygen feeding four RS-25 engines (~2 million lbs thrust), flanked by two five-segment Solid Rocket Boosters -- an evolution of the four-segment Shuttle design providing the total impulse required to approach Earth escape velocity.[10][11]

* Interim Cryogenic Propulsion Stage (ICPS) and Orion ESM: Atop the Core Stage sits the single-RL10-powered ICPS for perigee raising and orbital insertion, supporting the Orion Crew Module and its European Service Module (ESM), which houses the primary orbital maneuvering engine and 24 Reaction Control System (RCS) thrusters.[12][14]

Avcoat Heat Shield Forensics: Permeability and the Hybrid Loft Reentry

The primary technical risk resolved prior to the Artemis II rollout centered on Orion's 16.5-foot ablative heat shield, fabricated from Avcoat (epoxy novolac resin in a fiberglass honeycomb matrix).[16] During the 24,500 mph lunar-return reentry of uncrewed Artemis I, post-recovery inspections revealed unexpected cracking and spallation ("char liberation") across the ablative surface rather than uniform pyrolysis erosion.[16][18]

| Reentry Parameter | | Skip Entry (Artemis I Baseline) | | Modified Hybrid / Loft Entry (Artemis II) |

| Atmospheric Flight Path | | Initial atmospheric dip, exo-atmospheric skip phase, final reentry | | Steeper direct lift-modulated entry without prolonged exo-atmospheric skip |

| Thermodynamic Flux Profile | | Lower peak heat flux, prolonged low-heating dwell period | | Higher peak heat rate, significantly shorter integrated heating duration |

| Internal Pyrolysis Gas Dynamics | | Gas generation exceeds Avcoat char

permeability; internal pore pressure builds | | Rapid ablation keeps char surface permeable; prevents internal gas accumulation |

| Structural Outcome | | Blistering and localized char spallation observed on Artemis I[16] | | Suppresses pressure-driven spallation while maintaining cabin thermal margins[17][18] |

Forensic arc-jet testing and computational fluid dynamics pinpointed the root cause as a permeability-gas generation mismatch during the Artemis I "skip entry" trajectory.[18] During the extended low-heating dwell phase of the skip maneuver, internal Avcoat resin continued to pyrolyze and outgas faster than gases could vent through the partially sealed outer char layer, building subsurface pore pressure until chunks of char fractured away.[18] Rather than rebuilding the already-mounted Artemis II heat shield, NASA flight engineers modified the reentry trajectory to a steeper "hybrid/loft" profile that shortened the heating dwell time, ensuring continuous ablation and gas venting down to Pacific splashdown.[17]

Hybrid Free-Return Orbital Mechanics and ECLSS Validation

Rather than executing an immediate trans-lunar Hohmann transfer orbit out of Low Earth Orbit (LEO), Artemis II employed a risk-mitigated two-stage checkout architecture:[13]

* High Earth Orbit (HEO) Gate and Proximity Operations: After initial insertion into a 115 x 1,800-mile LEO, the ICPS raised apogee to ~68,000 miles for a high-orbit checkout.[13] Upon separating from the ICPS, Wiseman and Glover used Orion's Rotational and Translational Hand Controllers (RHC/THC) to turn the capsule around and station-keep within 300 feet of the spent ICPS -- validating manual RCS handling qualities critical for future docking at a cislunar Lagrange point (Gateway) or with the Starship Human Landing System.[14][20]

* Free-Return Lunar Flyby: Once life-support and propulsion systems passed verification in HEO, the Orion ESM main engine executed the Trans-Lunar Injection (TLI) burn, placing Orion Integrity onto a figure-eight circumlunar free-return trajectory.[13][15] Utilizing a passive lunar gravity assist carrying the crew to a human spaceflight distance record of 252,756 miles from Earth (~700,237 total mission miles), orbital mechanics naturally bent the spacecraft's trajectory back toward Earth reentry without requiring a lunar-vicinity engine burn.[15][13][19]

* Metabolic ECLSS and Radiation Shielding: With four astronauts aboard, Artemis II stress-tested the amine swing-bed carbon dioxide and moisture scrubbers across scheduled exercise and sleep cycles, while validating potable water dispensers, waste management, and real-time dosimetry via the Hybrid Electronic Radiation Assessor (HERA) and central stowage-bag storm shelter procedures against Van Allen belt protons and solar radiation events.[14][21][22][23]

Conclusion: From Pad 39B Rollout to Pacific Recovery

Following the January 17, 2026 rollout to Launch Pad 39B, NASA teams resolved liquid hydrogen interface leaks during the early February wet dress rehearsal and remediated an upper-stage helium quick-disconnect obstruction in March before launching Artemis II on April 1, 2026.[5][10] After executing the 10-day circumlunar

flight, Orion Integrity executed its hybrid loft reentry and splashed down in the Pacific Ocean off San Diego on April 10, 2026, at 8:07 p.m. EDT, where the crew and capsule were recovered by USS John P. Murtha.[9][19] By harmonizing heavy transport hydraulics with ablative aerothermodynamics and closed-loop life support, Artemis II established the operational foundation for sustained human exploration of the lunar surface.[12][13]

Updates... (Nov 22, 2026): Enriched all 23 citations (including NASA blogs, NTRS technical reports, OIG IG-24-011, TU Dresden IFK proceedings, and Journal of Space Weather and Space Climate) with verified publication dates, authors, and institutional attributions, removing bare access-only dates. (Earlier update, Nov 18, 2026: Updated the mission timeline from January 2026 rollout status to completed April 2026 flight record.)

Works Cited

* NASA (2026, January 16). Artemis II Moon Rocket Ready for Big Move. https://www.nasa.gov/blogs/missions/2026/01/16/artemis-ii-moon-rocket-ready-for-big-move/

* NASA (2026, January 14). Coverage, Briefing Set for NASA's Artemis II Moon Rocket Roll to Pad. https://www.nasa.gov/news-release/coverage-briefing-set-for-nasas-artemis-ii-moon-rocket-roll-to-pad/

* National Air and Space Museum (2023, April 3). Meet the Crew of Artemis II. Smithsonian Institution. https://airandspace.si.edu/stories/editorial/meet-crew-artemis-ii

* NASA Kennedy Space Center (2021, January). Crawler-Transporter 2 Fact Sheet. https://www.nasa.gov/wp-content/uploads/2021/01/crawler-transporter2_factsheet_508compliant.pdf

* NASA (2026, April 1). Artemis II Launch Day Updates. https://www.nasa.gov/blogs/missions/2026/04/01/live-artemis-ii-launch-day-updates/

* NASA (2016, September 1). Crawler Transporter Upgraded in Preparation for NASA's New Space Launch System Rocket. https://www.nasa.gov/general/crawler-transporter/

* R hlicke, I. (2016, March 10). Jacking and Equalizing Cylinders for NASA- Crawler Transporter. 10th International Fluid Power Conference (10. IFK), TU Dresden, Vol. 3, 307-318. https://tud.qucosa.de/api/qucosa%3A29398/attachment/ATT-0/

* Davis, V. L. (1975, August 1). Crawler Transporter Steering and JEL Systems. NASA Kennedy Space Center, NASA Technical Reports Server (19760012108). https://ntrs.nasa.gov/api/citations/19760012108/downloads/19760012108.pdf

* NASA (2026, April 10). Artemis II Flight Day 10: Live Re-Entry Updates. https://www.nasa.gov/blogs/missions/2026/04/10/artemis-ii-flight-day-10-re-entry-live-updates/

* Space.com (2026, April 10). Artemis 2 Splashdown: NASA hails Orion astronauts. https://www.space.com/news/live/artemis-2-nasa-moon-rocket-rollout-jan-16-2026

* NASA (2025, December). Space Launch System Reference Guide for Artemis II (SLS-5558). https://www.nasa.gov/wp-content/uploads/2025/12/sls-5558-artemis-ii-sls-reference-guide.pdf

* NASA (2025, April 8). NASA's First Flight With Crew Important Step on Long-term

Return to the Moon, Missions to Mars.
https://www.nasa.gov/missions/artemis/nasas-first-flight-with-crew-important-step-on-long-term-return-to-the-moon-missions-to-ma

* NASA (2026, April 1). Artemis II: NASA's First Crewed Lunar Flyby in 50 Years.
https://www.nasa.gov/mission/artemis-ii/

* SpaceDaily (2025, January 29). How to Operate NASA's Orion Spacecraft for Artemis II Mission.
https://www.spacedaily.com/reports/How_to_Operate_NASAs_Orion_Spacecraft_for_Artemis_II_Mission_999.html

* Space.com (2026, February 3; originally published August 18, 2022). NASA's Artemis 2 mission: Everything you need to know.
https://www.space.com/artemis-2-humans-moon-orbit

* NASA (2024, December 5). NASA Identifies Cause of Artemis I Orion Heat Shield Char Loss.
https://www.nasa.gov/missions/artemis/nasa-identifies-cause-of-artemis-i-orion-heat-shield-char-loss/

* Ad Astra (2024, December 13). NASA isn't fixing the heat shield on Artemis II.
https://www.adastraspace.com/p/artemis-ii-orion-heat-shield-root-cause

* AmericaSpace (2024, December 8). Artemis II Orion Heatshield Update.
https://www.americaspace.com/2024/12/08/artemis-ii-orion-heatshield-update/

* NASA (2026, April 10). Artemis II Splashdown and Recovery.
https://www.nasa.gov/gallery/artemis-ii-splashdown-and-recovery/

* NASA (2024, March 20). Key Test Drive of Orion on NASA's Artemis II to Aid Future Missions.
https://www.nasa.gov/humans-in-space/key-test-drive-of-orion-on-nasas-artemis-ii-to-aid-future-missions/

* NASA Office of Inspector General (2024, May 1). NASA's Readiness for the Artemis II Crewed Mission to Lunar Orbit (IG-24-011).
https://oig.nasa.gov/wp-content/uploads/2024/05/ig-24-011.pdf

* Hu, S., Barzilla, J. E., N ez, M., & Semones, E. (2025, January 7). Real-time dose prediction for Artemis missions. Journal of Space Weather and Space Climate, 15, 1,
https://doi.org/10.1051/swsc/2024037

* Broyan, J. L., Abercromby, A. F., Appelbaum, M. L., et al. (2024, August 16). Crew Health and Performance (CHP) Technology Roadmaps (ECLSS-CHP SCLT). NASA Technical Reports Server (20240009962).
https://ntrs.nasa.gov/api/citations/20240009962/downloads/CHP%20SCLT%20Technology%20Roadmaps%20-%20Public%20Relea