Space & Astronomy | Oct 31, 2026 | 5 min read | By Bryan White

How NASA Reconnected With Voyager 1 Across 15 Billion Miles Using a 1981 Backup Radio

Space & Astronomy * Voyager 1 * NASA

Cruising through interstellar space more than 15.4 billion miles (24.9 billion kilometers) from Earth -- where a radio signal traveling at the speed of light takes nearly 23 hours just to make a one-way trip -- NASA's Voyager 1 spacecraft is humanity's farthest-flung scientific outpost. Because the probe's three plutonium -238 radioisotope thermoelectric generators (RTGs) lose roughly 4 watts of electrical output every year as their radioactive fuel decays, mission engineers at NASA's Jet Propulsion Laboratory (JPL) must carefully balance every watt of power between keeping instruments warm and beaming data home. When a routine command to warm part of the spacecraft unexpectedly tripped an automated safety shutdown, Voyager 1 went silent on its main radio frequency -- forcing engineers to hunt for a whisper-faint backup transmitter that had not been used to talk to Earth since 1981.

1. Why a Routine Heater Command Triggered a Blackout

To prevent critical hardware from freezing in the deep cold of interstellar space, JPL flight controllers periodically send commands to toggle onboard electric heaters. However, when the flight team instructed Voyager 1 to turn on one of its heaters, the spacecraft's onboard fault-protection software -- an autonomous safety program designed in the 1970s to prevent battery or power-bus overload -- detected a voltage drop and intervened automatically.

Instead of shutting down the heater, the fault-protection routine followed its programmed priority list to save electricity: it first lowered the transmission rate of Voyager 1 's primary X-band radio transmitter , and when another fault check occurred days later, it powered the X-band transmitter off completely. Because every round-trip message takes nearly two full days (46 hours), engineers on Earth only discovered the silence when NASA's Deep Space Network (DSN) -- a global array of giant radio antennas in California, Spain, and Australia -- failed to detect the expected X-band carrier tone.

| Radio System | | Operating Frequency | | Beam Width & Power | | Operational History |

| Primary X-Band Transmitter | | ~8.4 GHz (3.6 cm wavelength) | | Focused narrow beam (higher power draw) | | Main science & engineering link across 15.4 billion miles |

| Backup S-Band Transmitter | | ~2.3 GHz (13 cm wavelength) | | Wider, fainter beam (lower power draw) | | Dormant since 1981 (post-Saturn flyby era) until fault fallback |

2. Catching a 1981 S-Band Whisper Across Interstellar Space

When the fault-protection routine shut off the primary X-band radio, it

automatically switched the spacecraft over to a secondary radio called the S-band transmitter , which uses less electrical power. While the S-band radio worked well when Voyager 1 flew past Jupiter in 1979 and Saturn in 1980, its lower frequency (~2.3 gigahertz) spreads its radio energy over a wider cone in space, making the signal dramatically fainter at Earth than the higher-frequency (~8.4 gigahertz) X-band beam.

Because Voyager 1 had not used its S-band transmitter since 1981 -- when the probe was less than 1 billion miles from Earth -- engineers were initially uncertain whether a signal now traveling more than 15 times farther could even be distinguished from cosmic background noise. By combining the collecting area of the giant 70-meter (230-foot) dish antennas of the Deep Space Network and scanning the predicted S-band frequency window, radio engineers successfully locked onto the faint carrier wave, confirming that the 47-year-old probe was still alive and stable.

3. Restoring Science Operations in the Interstellar Medium

Rather than immediately commanding the main X-band radio back on -- which could have re-triggered the same fault-protection loop -- JPL engineers used the low-rate S-band link to inspect Voyager 1 's power state and reset the computer routines that synchronize its onboard data systems. Once the underlying power-margin trigger was resolved, the flight team commanded the probe back to its primary X-band transmitter and resumed collecting measurements from its four remaining plasma, cosmic-ray, and magnetic-field instruments as Voyager 1 continues its journey toward the 50-year mark in deep space.

References & Primary Sources

* [1] NASA Jet Propulsion Laboratory (JPL). NASA's Voyager 1 Resumes Regular Operations After Communications Pause. -- https://science.nasa.gov/mission/voyager/

* [2] NASA Deep Space Network (DSN). Voyager 1 Interstellar Mission Status & Telemetry. -- https://eyes.nasa.gov/apps/dsn-now/dsn.html

* [3] Burlaga, L. F., Ness, N. F., Berdichevsky, D. B., et al. (2019). Magnetic field and particle measurements made by Voyager 2 at and near the heliopause. Nature Astronomy, 3, 1007-1012. -- https://doi.org/10.1038/s41550-019-0920-y